



Introduction

The AWS-825 is a PC-based industrial workstation designed especially for the factory floor and other harsh industrial environments. The highly-integrated AWS-825 features a 15" low radiation, high resolution CRT display and full-function keypads within a rugged compact unit.

The 19" AWS-825 can be either rack mounted or panel mounted. It provides 7 PCI/ISA slots or 8 ISA slots in a slide-out card cage (work drawer) for easy installation and maintenance.

An optional touchscreen is also available for a more intuitive user interface.

Specifications

- **Front panel:** Aluminum, meets NEMA4 or IP65
- **Disk drive housing:** Supports one 3.5" FDD, one 3.5" HDD and one slim CD-ROM (HDD and CD-ROM optional)
- **Three cooling fans:** 32 CFM fan for power supply, 29 CFM fan for monitor, 36 CFM fan for plug-in cards
- **Membrane keypad:** One with 39 operating keys, one with 10 function keys and 10 programmable macro function keys
- **Keyboard connector:** 5-pin DIN connector on both front panel and rear panel
- **Controls:** Reset and power On/Off
- **Indicators:** LEDs for power On/Off and HDD activity
- **Touchscreen:** Analog resistive type, and 35 million touch life with PC-bus controller
- **Dimensions (W x H x D):** 482 mm x 356 mm x 450 mm (19.0" x 14.0" x 17.7")
- **Gross Weight:** 38 kg (83.8 lbs)
- **Operating temperature:** 0 ~ 50° C (32 ~ 122° F)
- **Storage temp.:** -40° ~ 60° C
- **Storage humidity:** 5 ~ 95% non-condensing
- **Vibration (operation):** 5 ~ 17 Hz, double-amplitude displacement
17 ~ 500 Hz, 1.0 G peak to peak
- CE, FCC, BSMI, C-UL US compliant

Passive Backplane

- **PCA-6107P2:** 4 ISA, 2 PCI, 1 CPU slot
- **PCA-6108C:** 8 ISA slots


CRT Display

- **Size:** 15" diagonal
- **Resolution:** 1280 x 1024 max.
- **Dot pitch:** 0.28 mm
- **Horizontal frequency:** 30 ~ 60 kHz
- **Vertical frequency:** 44 ~ 100 Hz, noninterlaced
- MPR II compliant
- Power-on auto-degaussing
- Full digital video adjustment on rear panel

Power Supply

AC input 260 W (standard offer)

- **Input:** 85 ~ 130 V_{AC} or 180 ~ 260 V_{AC} switchable
- **Output:** +5 V @ 25 A; +12 V @ 9 A;
-5 V @ 0.5 A; -12 V @ 2.0 A
- **MTBF:** 100,000 hours
- **Safety:** UL/CSA/TÜV



Ordering Information

- AWS-825PB**
15" Monitor, PCA-6107P2, 260 W 110/220 V_{AC} power supply, 3.5" FDD
- AWS-825B**
15" Monitor, PCA-6108C, 260 W 110/220 V_{AC} power supply, 3.5" FDD
- AWS-825PB-T**
AWS-825PB + touchscreen (PC-bus interface)
- AWS-825B-T**
AWS-825B + touchscreen (PC-bus interface)

Accessories

- CDR-825-0024**
Slim 24X CD-ROM kit with support bracket
- PCA-6653**
ISA-bus VGA card with 1 MB VRAM, up to 1280 x 1024 @ 256 colors (for AWS-825B or AWS-825B-T only)
- PCA-6654LB**
PCI-bus VGA card with 2 MB EDO VRAM, up to 1280 x 1024 @ 64 K colors (for AWS-825PB or AWS-825PB-T only)

Note:
Products in the AWS-825B or AWS-825PB series do not include ISA or PCI VGA cards. We recommend purchasing the AWS-825B or AWS-825PB in conjunction with one of Advantech's CPU cards with on-board VGA. This solution will save you having to use an extra slot when integrating your system and is more cost-effective compared to buying a separate VGA card.

Alternatively, you can order a VGA card separately