

MIC-3645

Peripheral Boards

6U CompactPCI Ultra3 SCSI Interface Board

Features

- Dual SCSI channels
- 64-bit/32-bit, 33 MHz PCI bus
- Supports up to 16 LVD/SE devices on a wide SCSI bus
- LED indicators for easy monitoring of power and SCSI status



Specifications

Bus	PCI	64-bit/32-bit, 33 MHz	
SCSI	Interface	Ultra3	
	Controller	Symbios SYM53C1010-33	
	Max. Data Transfer Rate	160 MB/sec.	
	Channel	2	
Operating System	Compatibility	Windows 98/2000/NT, OS/2, SCO UNIX, UnixWare, Netware	
Power	Power Consumption	+ 3.3 V @ 2.0 A	
Environment		Operating	Non-Operating
	Temperature	0 ~ 50 °C (32 ~ 122 °F)	-40 ~ 60 °C (-40 ~ 140 °F)
	Humidity	--	95 % @ 60 °C, non-condensing
	Vibration (5-500 Hz)	1.0 Grms	2.0 Grms
Physical	Dimensions (W x D)	233.35 x 160 mm (9.2" x 6.3"), 1-slot wide	
	Weight	0.7 Kg (1.54 lb)	
Compliance	Standard	PICMG 2.0, R 3.0 CompactPCI Specifications	



MIC-3646
Rear Transition Board

Rear Transition Board

On-board Headers	SCSI x2
Rear Panel	SCSI x2

Ordering Information

Model Name	Descriptions
MIC-3645-A	6U CompactPCI Ultra3 SCSI Interface board with MIC-3646

CompactPCI Boards

ADVANTECH

• All brand names and registered trademarks are the property of their respective owner