

PT630-NRM Intel® Q57 ATX Board

PROCESSOR

- LGA 1156 socket for:
 - Intel® Core™ i7-860 2.80GHz/8M
 - Intel® Core™ i5-750 2.66GHz/8M
 - Intel® Core™ i5-660 3.33GHz/4M
 - Intel® Core™ i3-540 3.06GHz/4M
 - Intel® Pentium® G6950 2.80GHz/3M

CHIPSET

- Intel® chipset
 - Intel® Q57 (Ibex Peak)

SYSTEM MEMORY

- Four 240-pin DDR3 DIMM sockets
- Supports DDR3 1066/1333MHz
- Supports maximum memory bandwidth of 21GB/s in dual-channel mode when using DDR3 1333MHz
- Supports dual channel (128-bit wide) memory interface
- Supports up to 16GB system memory

EXPANSION SLOTS

- 1 PCI Express 2.0 x16 slot
- 1 PCI Express 2.0 x4 slot
- 2 PCI Express 2.0 x1 slots
- 3 PCI 2.3 33MHz slots

ONBOARD GRAPHICS FEATURES

- Intel Graphics Processing Unit
 - Supports 3D, 2D and video capabilities

Note: Both Intel® Core™ i7-860 and Core™ i5-750 CPUs does not support integrated graphics.

ONBOARD AUDIO FEATURES

- Realtek ALC262 2-channel High Definition Audio
- Two 24-bit stereo DACs and three 20-bit stereo ADCs
- S/PDIF input/output interface

ONBOARD LAN FEATURES

- One Realtek RTL8111DL PCI Express Gigabit controller
 - Supports 10Mbps, 100Mbps and 1Gbps data transmission
 - IEEE 802.3 (10/100Mbps) and IEEE 802.3ab (1Gbps) Compliant
- Integrated Intel® W82578DM LAN controller with external PHY for PCI Express LAN
 - IEEE 802.3
 - 10/100/1000 Mbps
 - Supports Jumbo frame

SERIAL ATA INTERFACE

- Supports 6 SATA (Serial ATA) interfaces which are compliant with SATA 1.0 specification
- SATA speed up to 3Gb/s (SATA 2.0)
- Supports RAID 0, 1, 5 and 10

INTEL ACTIVE MANAGEMENT TECHNOLOGY (AMT)

- Supports iAMT6.0
- Out-of-band system access
- Remote troubleshooting and recovery
- Hardware-based agent presence checking
- Proactive alerting
- Remote hardware and software asset tracking

TRUSTED PLATFORM MODULE (TPM) - optional

- Provides a Trusted PC for secure transactions
- Provides software license protection, enforcement and password protection

REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 2 COM ports
- 1 VGA port
- 1 DVI-I port (DVI-D signal only)
- 2 RJ45 LAN ports
- 4 USB ports
- Mic-in, line-in and line-out jacks

I/O CONNECTORS

- 4 connectors for 8 additional external USB 2.0 ports
- 2 connectors for 2 external COM ports
- 1 DIO connector
- 1 front audio connector
- 1 CD-in internal audio connector
- 1 S/PDIF connector
- 6 Serial ATA ports
- 1 FDD connector
- 1 24-pin ATX power connector
- 1 8-pin 12V power connector
- 1 chassis intrusion connector
- 1 front panel connector
- 2 fan connectors

BIOS

- AMI BIOS
- 64Mbit flash memory

ENERGY EFFICIENT DESIGN

- Supports ACPI specification 3.0
- Wake-On-Events include:
 - Wake-On-PS/2 Keyboard/Mouse
 - Wake-On-USB Keyboard/Mouse
 - Wake-On-LAN
- Enhanced Intel® SpeedStep Technology
- Dynamic FSB frequency switching

DAMAGE FREE INTELLIGENCE

- Monitors CPU/system temperature and overheat alarm
- Monitors V_{CORE}+5V/+12V/S_M+3.3V/V_{BAT} voltages and failure alarm
- Monitors CPU/system fan speed and failure alarm
- Read back capability that displays temperature, voltage and fan speed
- Watchdog timer function

TEMPERATURE

- 0°C to 60°C

HUMIDITY

- 10% to 90%

PCB

- ATX form factor
- 30.5cm (12") x 24.4cm (9.6")

REAR PANEL I/O PORTS

