

SPC-100A

10.4" TFT Smart Panel Computer with Intel XScale® CPU and Windows® CE .NET 4.2

NEW



Features

- SPC-100 offers a high graphic and networking performance platform
- Intel XScale® CPU IXP420 266/533 MHz optional, IXP420 533 MHz as default
- OS-Ready for Windows® CE .NET 4.2
- 10.4" TFT LCD Panel with resistive touch screen
- High networking performance, wire-speed packet processing performance
- Comprehensive I/O interface with Ethernet, USB, RS-232, Audio, Video-in (Optional). Also integrated Mini-PCI interface and antenna for WLAN device
- Bezel-mount model: Ideal design for outside-in mounting type
- IP65 approved for front bezel

Introduction

The SPC-100 series integrates Intel's RISC XScale IXP420-533 MHz processor and Windows CE .NET 4.2. It is designed to provide customers with a high computing power embedded display platform with good networking and graphic performance. Each Panel Computer incorporates a high-performance Intel XScale core with additional Network Processor Engines (NPEs) to achieve wire-speed packet processing performance. The SPC-100 series also integrates the SMI501 graphic controller to provide good graphic capabilities for multimedia applications.

Specification

System Kernel

- **CPU** Intel IXP-420 533 MHz on board
- **OS** Windows CE .NET 4.2 professional plus
- **SDRAM** 64 MB SDRAM on board
- **Flash** 32 MB Flash memory on board
- **WDT** IXP420 internal
- **Boot Loader** 1 MB AMD Flash ROM for boot loader
- **System Control** HW reset
- **RTC** HT1381, backup by internal backup battery

Display

- **LCD** AUO 10.4" TFT LCD SVGA 800 x 600
- **Touch Screen** 4-wire resistive touch screen as default, 5-wire resistive touch screen is optional
- **VGA Chip** SMI 501 VGA chip with 8 MB VRAM

I/O

- **Mini PCI** 1 x Mini PCI slot
- **RS-232** 2 x full function transceiver level RS-232 by DB-9 connector. 1 x 4-wire transceiver level RS-232 by DB-9 connector. 1 x 4-wire transceiver level RS-232 by pin-header inside the case
- **RJ-45** 1 x 10/100Base-T RJ-45
- **USB** 4 x USB 1.1 host
- **PCMCIA** 1 x PCMCIA slot type II
- **Video-in** TV-in function is optional
- **Audio** 1 x Audio line-out jack; speaker out pin header inside case

Power

- **V-in Range** DC 10V ~ 28V
- **Protection** Power surge protection, Electrical pole reversal protection
- **System Backup Battery** Rechargeable Li-ion battery 65 mAh support system SDRAM and RTC
- **Power Switch** 1 x power switch
- **Power Connector** 3-pin power connector with screw hole
- **Power Consumption** 10.4 W (Typical power consumption w/ OS running and LCD backlight on)


Mechanical

- **Material** Front bezel is aluminum, others are made from SPCC
- **Mounting** SPC-100A can be mounted on walls less than 4mm thick

Environment

- **Operating Temp** 0 ~ 50° C
- **Storage Temp** -20 ~ 60° C
- **Water/Dust Resistance** IP65 front bezel
- **Certification** CE/ FCC, UL

Dimensions



Ordering Information

- **SPC-100A-545CE1** Intel XScale® CPU IXP420 533 MHz CPU, Windows CE .NET 4.2 professional plus pre-installed with aluminum front-bezel ,10.4" color TFT LCD, and resistive touch screen SPC. (Bezel-mount Model)
- **SPC-POWERSET** 60 W power adapter with 3-Pin power connector (Customer must purchase power cord separately)

Packing List

- Smart Panel Computer
- Windows CE.NET end user license agreement (for Windows CE.NET version)
- CD-ROM
 - 1) Readme.txt
 - 2) User's manual
 - 3) Data Sheet
 - 4) Upgrade utility
 - 5) Microsoft ActiveSync Version 3.7 installation files (Windows CE.NET)
 - 6) Windows CE.NET 4.2 platforms SDK (Windows CE.NET)
- Warranty Card
- 1 x USB client ActiveSync cable
- 3-pin power connector with screw hole