

SPC-64A

6.4" TFT Smart Panel Computer with Intel XScale® CPU and Windows® CE .NET

NEW



Features

- Intel XScale® PXA255 400 MHz CPU and Windows CE .NET OS
- 6.4" color TFT LCD panel and resistive touch screen
- Ultra low power consumption and fanless
- Compact size
- IP65 front bezel
- Can operate without back cover/removable back cover for user
- Bezel-mount model, front bezel is made from aluminum, ideal for outside-in mounting type

Introduction

The SPC-64A integrates the Intel® XScale PXA255 400 MHz processor and Windows® CE .NET 4.2 or Embedded Linux (Embedded Linux will support by project based). It is designed to provide customers with a low power, higher performance embedded display platform with good networking and graphic performance. SPC-64A has a bright VGA (640 x 480) LCD screen and comes with an elegant front aluminium bezel for outside-in mounting.

Specification

System Kernel

- **CPU** Intel PXA255 400 MHz on board
- **OS** Windows CE .NET 4.2
- **SDRAM** 64 MB SDRAM on board
- **Flash** 32 MB Flash memory on board
- **WDT** PXA255 internal
- **Boot Loader** 1 MB AMD Flash ROM for boot loader
- **RTC** HT1381

Display

- **LCD** 6.4" TFT VGA 640 x 480
- **Touch Screen** 4-wire resistive touch screen
- **VGA Chip** TVIA 5202G VGA chip with 8 MB SDRAM

I/O

- **RS-232** 1 x full function transceiver level RS-232 by DB-9 connector,
2 x full function transceiver level RS-232 by pin-header inside the case
- **RS-485** 1 x RS-485 by DB-9 connector
- **RJ-45** 1 x 10/100Base-T RJ-45
- **USB** 2 x USB host; 1 x USB client
- **PCMCIA** 1 x PCMCIA slot type II
- **CF** 1 x CF slot type II
- **Digital I/O** 8 DI & 8 DO. Pin header output inside the case. Provide API to access DIO
- **GPIO** 8 GPIO. Pin header output inside the case. Default as hotkey
- **Audio** 1 x Audio line-out jack

Power

- **V-in Range** DC 10 V ~ 28 V
- **Protection** Power surge protection
Electrical pole reversal protection
- **SM Bus** For smart battery, pin headers, I2C bus
- **System Backup Battery** Rechargeable Li-ion battery 65 mAh for RTC
- **Power Switch** 1 power switch
- **Power Conn** 3-pin power connector with screw hole
- **SW Reset** Execute S/W reset through system configuration
- **Power Consumption** 8 W (Typical power consumption w/ OS running and LCD backlight on)

Mechanical

- **Dimension** Box size: 192.5 mm x 139 mm x 37.8 mm
Front bezel: 218.5 mm x 165 mm x 8 mm
- **Material** Front bezel is aluminum, others are made from SPCC
- **Mounting** SPC-64A can be mounted on walls less than 4mm thick


Environment

- **Operating Temp** 0 ~ 50° C
- **Storage Temp** -20 ~ 60° C
- **Water/Dust Resistance** IP65 front bezel
- **Certification** CE/FCC/UL

Ordering information

- **SPC-64A-445CE1** Intel XScale PXA255 400MHz CPU, Windows CE .NET pre-installed with 6.4" color TFT LCD, resistive touch screen and aluminum front bezel
- **SPC-POWERSSET** 60 W power adapter with 3-pin power connector (Customer must purchase power cord separately)

Dimensions



Packing List

- Smart Panel Computer
- Windows CE .NET end user license agreement (Windows CE .NET version)
- CD-ROM
 - 1) Readme.txt
 - 2) User's manual
 - 3) Data Sheet
 - 4) Upgrade utility
 - 5) Microsoft ActiveSync Version 3.7 installation files (Windows CE .NET)
 - 6) Windows CE .NET 4.2 platforms SDK (Windows CE .NET)
- Warranty Card
- 1 x USB client ActiveSync cable
- 3-pin power connector with screw hole